


M16

Quad Band GSM/GPRS Module



▶ Quad Band

▶ GPRS Multi-slot Class 12

▶ Extended Temperature Range -45 °C to +85 °C

▶ Embedded Internet Services Protocols

▶ RoHS Compliant


▶ Serial Port Multiplexer (GSM0710)

▶ Quectel Enhanced AT Commands

The M16 is a complete Quad-band GSM/GPRS solution in a ZIF connector type which can be embedded in customer application, offering the highest reliability and robustness.


Featuring an industry-standard interface, the M16 delivers GSM/GPRS 850/900/1800/1900MHz performance for voice, SMS, data, and fax in a form factor with extremely low power consumption. With a configuration of 54.5mm x 36mm x 4.5mm, M16 can fit into almost all the M2M applications, including VTS, Smart Metering, Wireless POS, Security, etc.

- Quad - band GSM/GPRS module with a size of 54.5mmx36mmx4.5mm
- ZIF connector suits for customer application
- Embedded powerful Internet service protocols
- Based on mature and field-proven platform, backed up by our support service, from definition to design and production



M16

Quad Band GSM/GPRS Module



General Features

Quad-Band	850/ 900/ 1800/ 1900 MHz
GPRS Multi-Slot Class	12/10/8
GPRS Mobile Station	Class B
Compliant To GSM Phase 2/2+	Class 4 (2W @850/ 900 MHz) Class 1 (1W @1800/1900MHz)
Supply Voltage Range	3.4~4.5 V 4.0V nominal
Low Power Consumption	1.1mA @ DRX=5 0.7mA @ DRX=9
Operation Temperature	-45 °C to +85 °C
Dimensions	54.5mmx36mmx4.5mm
Weight	Approx 12g
Control via AT Commands	GSM 07.07 ,07.05 Enhanced AT commands SIM application toolkit

Specifications for Fax and Data

Fax	Group 3, Class 1 & 2
GPRS Class 12	Max. 85.6 kbps (uplink & downlink)
PBCCH Support	
Coding Schemes	CS 1, 2, 3, 4
CSD	Up to 14.4 kbps
USSD	
Non Transparent Mode	
Protocols	PPP TCP/IP HTTP FTP MMS

Specifications for SMS via GSM / GPRS

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Specifications for Voice

Speech Codec Modes	Half Rate (HR) Full Rate (FR) Enhanced Full Rate (EFR) AMR Half Rate AMR Full Rate
Echo Arithmetic	Echo Cancellation Echo Suppression Noise Reduction
Hands-Free Operation	

Interfaces

Hirose 40-Pin ZIF Connector	
Power Supply	
External SIM	3V/1.8V
Analog Audio Interfaces	Two channels
Serial Interface	One
Antenna Connector And Solder Pad	

Compatibility

Drivers	MUX Driver
Compatibility	AT cellular command interface

Approvals

CE FCC GCF PTCRB China TA

Quectel Wireless Solutions

Address :Room 801, Building E, No.1618,
Yishan Road, Shanghai, China

Tel : +86 21 51082965

Fax: +86 21 64058005

Web: <http://www.quectel.com/>

Email : info@quectel.com